

21,000-Gallon Frac Tank



Mobile Storage Tank

Specifications

Dimensions	45 ft. (13.72 m) long x 8 ft. 6 in. (2.59 m) wide x 11ft. (3.35 m) high, including towing assembly
Weight	28,000 lb. (12700.59 kg)
Capacity	21,000 gal. (79493.65 l) (nominal)
Valves	Two 4 in. (10.16 cm) butterfly valve drains with NPT threads, one at each end in recessed sumps One 4 in. (10.16 cm) valve mid-way on tank front
Manways	Two to three 21–25 in. (53.34– 63.50 cm) manways, typically at front, side and rear All manways equipped with butterfly-style nuts
Inspection Hatch	One 21 in. (53.34 cm) top inspection hatch with safety bars
Fill/Overflow Line	Top 3 in. (7.62 cm) feed line with cap and NPT threads
Vent	4 in. (10.16 cm) vent/hatch equipped with pressure relief valve 4 or 16 oz. (113.40 g or 453.59 g) psi for pressure, 0.4 oz. (11.34 g) psi for vacuum
Other Connections	Additional 4 in. (10.16 cm) and 2 in. (5.08 cm) NPT connections with caps

Options & Accessories

- Secondary Containment Berm
- Steam Coils
- Epoxy or Non-Coated Interiors
- Camlock Fittings
- Vapor-Tight
- Suction and Discharge Hoses
- Level Gauges

Specifications are approximate and may vary. Ask your sales representative for specific dimensions for the unit we supply to you.

