

10,000-Gallon Mini Frac Tank



Mobile Storage Tank / Portable Tank

Specifications

Dimensions	22–24 ft. (7.92 m) long x 8 ft. 6 in. (2.59 m) wide x 8 ft. 7 in. (2.62 m) high
Weight	14,000 lb. (6350.29 kg)
Capacity	10,000 gal. (37854.12 l) (nominal)
Valves	Two 4 in. (10.16 cm) butterfly valve drains with NPT threads, one at each end in recessed sumps
Manways	Two 21–25 in. (53.34–63.50 cm) manways, typically at side and rear All manways equipped with butterfly-style nuts
Inspection Hatch	One 21 in. (53.34 cm) top inspection hatch with safety bars
Fill/Overflow Line	Top 3 in. (7.62 cm) feed line with cap and NPT threads (availability varies)
Vent	4 in. (10.16 cm) vent/hatch equipped with pressure relief valve 16 oz. (453.59 g) psi for pressure, 0.4 oz. (11.34 g) psi for vacuum
Roll-Off Structure	6 in. (15.24 cm) x 2 in. (5.08 cm) x 1/4 in. (0.635 cm) Rails 36 in. (91.44 cm) Inside Dimension
Other Connections	Additional 4 in. (10.16 cm) and 2 in. (5.08 cm) NPT connections with caps

Options & Accessories

- Secondary Containment Berm
- Non-Coated Interior
- Camlock Fittings
- Suction and Discharge Hoses
- Level Gauges

Specifications are approximate and may vary. Ask your sales representative for specific dimensions for the unit we supply to you.

