

6,300-Gallon Crosslinked Polyethylene Roll-Off Tank



Poly Tank

Specifications

Dimensions	Poly tank	16 ft. 3 in. (4.95 m) long x 8 ft. (2.44 m) wide x 7 ft. 4 in. (2.24 m) high
	Overall	20 ft. 8¾ in. (6.32 m) long x 8 ft. 6 in. (2.59 m) wide x 8 ft. 6½ in. (2.60 m) high (handrails down) 11 ft. 9 in. (3.58 m) high (handrails up)
Weight		10,600 lb. (4808.08 kg)
Valves		Two 4 in. (10.16 cm) butterfly valves with NPT threads, both on low end of the tank
Access Panels		Two 24 in. (60.96 cm) bolted panels provide access for cleaning, one 6 in. (15.24 cm) access port
Vent		One 8 in. (20.32 cm) flanged PVC vent cap
Roll-off Structure		6 in. x 2 in. x 1/4 in. (15.24 cm x 5.08 cm x 6.35 mm) rails, 36 in. (91.44 cm) inside dimension
Other Connections		Two 3 in. (7.62 cm) bulkhead fitted connections with NPT threads
Lifting Lugs		Four (one on each corner)

Options & Accessories

- Butterfly valve bodies in PVC or Polypropylene
- Butterfly valve seals in EPDM, Buna-N or Viton
- Butterfly valve disks in PVC or Polypropylene
- Butterfly valve flanges in PVC or Polypropylene
- Secondary Containment Berm
- Level Gauges

Specifications are approximate and may vary. Ask your sales representative for specific dimensions for the unit we supply to you.

